

New England Survey Activity

Mariners Briefing

Date of Notice: July 8, 2019

Notice No. 019

Overview

These briefings are intended to update mariners on marine operations for the Bay State Wind survey activities. Survey operations are planned for locations throughout the lease area (see chart) and are expected to last several months. These operations involve only the survey phase of the projects.

Mariners briefings are submitted as needed to the U.S. Coast Guard and distributed to the fishing community and interested mariners on our website at: us.orsted.com/mariners or via email upon request through Rodney Avila (RODAV@orsted.com).

Vessels will designate a working channel on VHF 16 daily at 0600 and 1800

About the Wind Farms

Bay State Wind (BSW), a 50-50 joint venture between Ørsted and Eversource, is a planned offshore wind farm located 14 miles south of Martha's Vineyard. BSW will contain an offshore substation, and a subsea transmission system able to deliver clean energy to the New England electrical grid.

Revolution Wind, a 50-50 joint venture between Ørsted and Eversource, is a planned offshore wind farm located 15 miles south of the Rhode Island coast. Revolution Wind will contain an offshore substation, and a subsea transmission system able to deliver clean energy to the New England electrical grid.

Ongoing BSW Survey Activities

- Projected Beginning: April 2019
- Projected End: July 2019

Ongoing Rev Survey Activities

- Projected Beginning: June 2019
- Projected End: August 2019

Contact

For fisheries related inquiries:

Rodney Avila

Corporate Fisheries Liaison

Phone: 857.332.4479

Email: RODAV@orsted.com

John O'Keeffe

Director Marine Affairs

Phone: 857.332.4485

Email: JOHNO@orsted.com

Julia Prince

CT/NY Fisheries Liaison

Phone: 857.348.3263

Email: JULPR@orsted.com





Conti

MV Conti is used for geotechnical surveying. It employs a dynamic positioning system to maintain position when on site.

Flag: USA
LOA: 210 ft
Beam: 54 ft
DWT: 2346 mt

Call Sign: WDD3645
IMO: 9285299



Regulus

MV Regulus is used for geotechnical surveying. It employs a dynamic positioning system to maintain position when on site.

Flag: USA
LOA: 272 ft
Beam: 58 ft
DWT: 3580 mt

Call Sign: WGD2987
IMO: 9582324



Gargano

MV Gargano is used for geotechnical surveying. It employs a dynamic positioning system to maintain position when on site.

Flag: British
LOA: 236 ft
Beam: 52 ft
DWT: 2244 mt

Call Sign: VSMW5
IMO: 9249403



Enterprise

MV Enterprise is used for geophysical surveying.
Flag: USA
LOA: 170 ft
Beam: 40 ft

Call Sign: WDD9388
IMO: 9473585



Kommandor Iona

MV Commander is used for geophysical surveying.

Flag: UK
LOA: 238 ft
Beam: 48 ft

Call Sign: GAAK
IMO: 8401999



Discovery

MV Discovery is used for geophysical and geotechnical surveying.

Flag: Panama
LOA: 230 ft
Beam: 41 ft

Call Sign 3EKE6
IMO 9152882

*Expected survey vessels / subject to change

Vessel Name	Site Function	Project	Date/Activity	Projected Outlook
Conti	Geotechnical survey vessel	Bay State Wind	Vessel demobilized	Vessel demobilized
Regulus	Geotechnical survey vessel	Bay State Wind	Vessel demobilized	Vessel demobilized
Cargano	Geotechnical survey vessel	Bay State Wind	Vessel demobilized	Vessel demobilized
Enterprise	Geophysical survey vessel	Revolution Wind	July 8 / Vessel will continue survey operations in the lease area	Wx dependent / Vessel will continue survey activities in the lease area
Discovery	Geophysical survey vessel	Revolution Wind	July 8 / Vessel will continue survey operations in the lease area	Wx dependent / Vessel will continue survey activities in the lease area
Kommander Iona	Geophysical survey vessel	Revolution Wind	July 8 / Vessel is undergoing off-shore mobilization in lease area	Following completion of mobilization, Vessel will begin survey operations

All Mariners transiting or fishing in the survey area are requested to give a wide berth to survey vessels as they may be limited in their ability to maneuver (VRAM) and towing gear out to 300 meters behind the vessel. Vessels in the vicinity of the survey vessels should operate in a manner that will not endanger the vessel or associated equipment

